

CISCO(TM) COMPATIBLE (GLC-SX-MM) GE SFP 1000MB SX MINI-GBIC 30-1301-02



Lengths Available:			
Colors Available:			
Part Numbers this model:	BE-190517		
Sales Category:	Fiber Optic Jumpers	Wire Gauge (AWG):	Not Specific / Not Applicable
Connector A:	Fiber Optic SFP Connector	Specification:	
Connector B:	Fiber Optic SFP Connector	Number Ports:	N/A
Export Tariff Code (HST):	3917230000	Transfer Rate:	

Feature / Style:		Images Length/Size Shown:	EA
# Positions:		Shielding:	
Convert From/To:		Type:	HDMI to AV

The Cisco(TM) compatible GLC-SX-MM-OEM modules offer customers a wide variety of 10 Gigabit Ethernet connectivity options for data center, enterprise wiring closet, and service provider transport applications. The 1000BASE-SX SFP, compatible with the IEEE 802.3z 1000BASE-SX standard, operates on legacy 50um multimode fiber links up to 550 m and on 62.5 Åµm Fiber Distributed Data Interface (FDDI)-grade multimode fibers up to 220 m. It can support up to 1km over laser-optimized 50um multimode fiber cable.

1.25GBd SFP (Small Form Pluggable) Short Wavelength (850nm) Transceiver

Features:

- Up to 1.25 GBd bi-directional data links
- Compliant with IEEE 802.3z Gigabit Ethernet and 1000BASESX and SFP MSA
- Hot-pluggable SFP footprint
- 850nm VCSEL laser transmitter
- Duplex LC connector
- Built-in digital diagnostic functions
- Up to 550m on 50/125um MMF
- Up to 300m on 62.5/125um MMF
- Single power supply 3.3V
- Compatible for use on all specified Cisco Switches
- RoHS Compliance
- Class 1 laser product complies with EN 60825-1
- Operating temperature range: 0C to 70C

NOTE: Cisco is TRADEMARK Cisco Corp