

CISCO(TM) COMPATIBLE (GLC-T) 1000 BASE-T SFP COPPER 100 METER 30-14 TRANS



Lengths Available:			
Colors Available:			
Part Numbers this model:	BE-190519		
Sales Category:	Fiber Optic Jumpers	Wire Gauge (AWG):	Not Specific / Not Applicable
Connector A:	Fiber Optic SFP Connector	Specification:	
Connector B:	Fiber Optic SFP Connector	Number Ports:	N/A
Export Tariff Code (HST):	8525503035	Transfer Rate:	

Feature / Style:		Images Length/Size Shown:	EA
# Positions:		Shielding:	
Convert From/To:		Type:	HDMI to AV

The Cisco(TM) compatible GLC-LH-SM-OEM modules offer customers a wide variety of 10 Gigabit Ethernet connectivity options for data center, enterprise wiring closet, and service provider transport applications. The Cisco compatible GLC-T-OEM 1000BASE-T SFP operates on standard Category 5 unshielded twisted-pair copper cabling of link lengths up to 100 m (328 ft). The compatible 1000BASE-T SFP modules support 10/100/1000 auto negotiation and Auto MDI/MDIX.

1000BASE-T SFP (Small Form Pluggable) Copper Transceiver 3.3V, 1.25GBd Gigabit Ethernet

Features:

- Up to 1.25 GBd bi-directional data links
- Compliant with IEEE 802.3z, IEEE 802.3u, IEEE 802.3ab compliant and SFP MSA
- Hot-pluggable SFP footprint
- Support 1000BASE-T full duplex default operating mode
- Support 10/100/1000BASE-T operation in host systems with SGMII interface
- RJ-45 connector
- Auto-sense MDI/MDIX
- Compatible for use on all specified Cisco(TM) Switches
- Single power supply 3.3V
- RoHS Compliance
- Operating temperature range: 0C to 70C.

NOTE: Cisco is TRADEMARK Cisco Corp