

MyCableMart.com

Your Home Theatre Connectivity Experts

6224 Bury Dr, Eden Prairie MN 55346 P. 952-486-8736

CAT5E ETHERNET RJ45 PATCH CABLE, STRANDED, SNAGLESS BOOTED, WHITE



Lengths Available:	6in, 1ft, 2ft, 3ft, 4ft, 5ft, 6ft, 7ft, 10ft, 14ft, 15ft, 20ft, 25ft, 30ft, 50ft, 100ft,		
Colors Available:	Black, Blue, Gray, Green, Orange, Purple, Red, White, Yellow,		
Part Numbers this model:	BE-100516WT, BE-100501WT, FE-C5-02-WHI , HA-C5-03-WHI, BE-100500WT, BE-100504WT, BE-100513WT, HA-C5-07-WHI, FE-C5-10-WHI, FE-C5-14-WHI, BE-100507WT, BE-100514WT, FE-C5-25-WHI, FE-C5-30-WHI, BE-100509WT, BE-100511WT,		
Sales Category:	CAT 5E Networking Cables	Wire Gauge (AWG):	26 AWG
Connector A:	RJ45 Ethernet Male	Specification:	
Connector B:	RJ45 Ethernet Male	Number Ports:	N/A
Export Tariff Code (HST):	8544422000	Transfer Rate:	
Feature / Style:		Images Length/Size Shown:	2 FT
# Positions:	8p8c (RJ45, Ethernet)	Shielding:	Unshielded
Convert From/To:		Type:	

Connects any CAT5 or CAT5E (Enhanced) application such as computer to hub, patch panel or wall jack. This 350MHz CAT5E PVC stranded patch cord meets TIA/EIA 568A specifications, and support all CAT5E and other high speed applications. Uses stranded wires for added cable flexibility.

Technical Specifications:

- 26AWG Copper twisted pairs
- Suitable for any 10Mbit, 100Mbit network standards up to 330ft segment runs
- 350 Mhz Category 5E, exceed IEEE standards suitable for 100Mbit networks. May support 1Gbps in shorter lengths
- Unshielded Twisted pairs (UTP) suitable for most business and home network installations
- CM NEC Rated for In-wall installation (Home or business)
- Meets EIA/TIA TSB-40A for Stranded 568B standards
- 50u Gold Plated contacted
- Molded Strain Relief boot connectors
- RoHS Compliant
- See TECH DOC for drawing and additional technical information
- NOT UL Listed, but meets UL standards