

## COMPONENT (YPBPR) VIDEO AND AUDIO ANALOG TO HDMI DIGITAL CONVERTER



<b>Lengths Available:</b>			
<b>Colors Available:</b>			
<b>Part Numbers this model:</b>	FE-ADT-471		
<b>Sales Category:</b>	HDMI Switch/Boosters	<b>Wire Gauge (AWG):</b>	Not Specific / Not Applicable
<b>Connector A:</b>	RCA/Phono Female	<b>Specification:</b>	
<b>Connector B:</b>	RCA/Phono Female	<b>Number Ports:</b>	N/A
<b>Export Tariff Code (HST):</b>	8525503035	<b>Transfer Rate:</b>	
<b>Feature / Style:</b>		<b>Images Length/Size Shown:</b>	EA
<b># Positions:</b>		<b>Shielding:</b>	
<b>Convert From/To:</b>		<b>Type:</b>	

This product converts HDMI into YPbPr (color difference) and left and right channel output, supports full hd 1080p resolution, and enables Blu ray DVD or PS3, PS4, X box and other HD devices to display their own images on TV with YPbPr and convert them into R / L audio after conversion. Converter entertainment center, HDTV retail and exhibition venues, HDTV, projectors, noise space and safety issues, data heart control, information distribution, conference room presentations, school solutions and business training environment.

It is the YPbPr (color difference) and left and right channels into HDMI output, support for Full HD 1080P resolution, let PC Users show their image not only on the monitor of the PC, but also on the TV, the conversion is with R / L audio. The number provided by the converter Entertainment centers, HDTV retail and display venues, HDTVs, set-top boxes, DVDs and projectors, noise space and security issues, data Heart Control, Information Assignment, Conference Room Presentations, Solutions for Schools and Business Training Environments.

### Features and Specifications:

- Power: 5V1A
- Input: HDMI signal, bandwidth 165M, HDMI1.3 compatible
- Output: YPBPY signal output with the same resolution as the input HDMI signal, stereo sound signal output
- YPBPR signal impedance matching: 75 ohm
- Support HDMI input format is as follows:
- 480P (60Hz), 576P (50Hz), 720P (50 / 60Hz), 1080i (50 / 60Hz)
- Support YPbPr output format is as follows:
- 480P (60Hz), 576P (50Hz), 720P (50 / 60Hz), 1080i (50 / 60Hz)
- Easy to use: install in a few seconds, no need to set.
- Converts the complete YPbPr + L / R audio to HDMI output.
- Supports HDCP1.2
- Each channel supports 165MHz / 1.65Gbps (6.75Gbps all channels) bandwidth HDMI output.
- Supporting real analog video output up to UXGA and 1080p, 10-bit DAC
- LED signal and power mode.
- Power supply (5V 1A)
- YPbPr Input : 1080p/1080i/720p/576p/576i/480p/480i