MyCableMart_com

Your Home Theatre Connectivity Experts 6224 Bury Dr, Eden Prairie MN 55346 P. 952-486-8736

HIGH SPEED 4K@60HZ HDMI CABLE 18GBPS 30AWG GOLD PLATED





Lengths Available: 8in, 1.5ft, 3ft, 6ft, 8ft, 10ft, 12ft, 15ft, 20ft, 25ft, 30ft, 35ft, 40ft, 50ft,

Colors Available:

Part Numbers this model:	FE-HH14-8IN, GC-HH14-01, GC-HH14-03, GC-HH14-06, HA-HH14-08, GC-HH14-10, GC-HH14-12, GC-HH14-15, GC-HH28-20, GC-HH28-25, GC-HH28-30, GC-HH26-35, GC-HH26-40, GC-HH26-50,		
Sales Category:	HDMI Cables	Wire Gauge (AWG):	30 AWG
Connector A:	HDMI Standard Type A Male	Specification:	
Connector B:	HDMI Standard Type A Male	Number Ports:	N/A
Export Tariff Code (HST):	8544422000	Transfer Rate:	
Feature / Style:		Images Length/Size Shown:	3 FT
# Positions:		Shielding:	Double Shi
Convert From/To:		Туре:	Round

Connect any Blu-Ray player, Satellite Box, Cable Box, DVD Player, Media Player, or ANY device accepting the standard HDMI connector. All our HDMI cables are manufactured to specific HDMI LLC standards and have passed stringent HDMI version 2.0 ATC testing requirements.

Supports the following features that are included in the HDMI Version 2.0 specification:

- 4K x 2K Support Supports ANY resolution to 4K (4096x2160) at 30/60Hz
- HDMI Ethernet Channel (HEC) Delivers Ethernet data interconnectivity to compatible devices through the HDMI port so you don't need extra cables to get extended features
- Audio Return Channel ARC Allows the HDMI connection between a television and A/V receiver to transmit audio two ways, both upstream and downstream.
- Full 3D Support If your source and receiving device support 3D, this cable will!
- 18 Gbps Total Bandwidth (independently lab tested by Agilent Technologies to the HDMI v2.0 specification
- Support for ANY TV refresh rates (such as 120Hz/240/480/600Hz), HDCP 1.2 and 2.2 Support Cable Specifications:
- Wire Gauge: 30 AWG
- Gold Plated 1u (All 19 wires and Ground Shroud)
- Silver-plated (20u) PURE copper wire for maximum conductivity WITHOUT any harmful lead (RoHS)
- Triple Shielded, EMI (Foil, braid, foil)
- No bulky, unnecessary ferrites cores
- UL / CSA listed (UL File #: E329703, Style: 20276), Max Temperature: 80 C
- Fully HDMI LLC / ATC Certified to Version 2.0 testing specifications.