

## 10FT PREMIUM XLR 3P MALE/FEMALE MICROPHONE / AUDIO MIXER CABLE



<b>Lengths Available:</b>	3ft, 6ft, 10ft, 15ft, 25ft, 50ft, 75ft, 100ft,		
<b>Colors Available:</b>			
<b>Part Numbers this model:</b>	FE-PRXLR-03MF, FE-PRXLR-06MF, <b>FE-PRXLR-10MF</b> , FE-PRXLR-15MF, FE-PRXLR-25MF, FE-PRXLR-50MF, FE-PRXLR-75MF, FE-PRXLR-100MF,		
<b>Sales Category:</b>	XLR / TRS Cables	<b>Wire Gauge (AWG):</b>	18 AWG
<b>Connector A:</b>	XLR (3-Pin) Male	<b>Specification:</b>	
<b>Connector B:</b>	XLR (3-Pin) Male	<b>Number Ports:</b>	N/A
<b>Export Tariff Code (HST):</b>	8544422000	<b>Transfer Rate:</b>	
<b>Feature / Style:</b>		<b>Images Length/Size Shown:</b>	10 FT
<b># Positions:</b>	3	<b>Shielding:</b>	Shielded
<b>Convert From/To:</b>		<b>Type:</b>	Round

The XLR connector is a style of electrical connector, primarily found on professional audio, video, and stage lighting equipment such as microphones and audio mixers. The connectors are circular in design and have between 3 and 7 pins. They are most commonly associated with balanced audio interconnection, including AES3 digital audio, but are also used for lighting control, low-voltage power supplies, and other applications. XLR connectors are available from a number of manufacturers and are covered by an international standard for dimensions, IEC 61076-2-103.[1] They are superficially similar to the older and smaller DIN connector range, but are not physically compatible with them.

Our PREMIUM line of XLR cables feature balanced copper 18AWG wires and full end-to-end shielded for the absolute best quality performance.

### Specifications:

- XLR 3P Male to XLR 3P Female
- Black PVC Jacket
- Wire gauge: 18AWG
- Copper Wires
- Shielding: Aluminum foil + 128/0.1 copper braid
- Black metal housing
- Secure snap connectors
- Gold plated conductors
- OD: 6.5mm