

PREMIUM SHIELDED 3.5MM 4 CONDUCTOR TRRS/3 BAND+MIC OR VIDEO M/M CABLE



Lengths Available:	6in, 1ft, 3ft, 6ft, 10ft, 12ft, 15ft, 20ft, 25ft, 35ft, 50ft,		
Colors Available:			
Part Numbers this model:	FE-PX4CT-MM-6IN, FE-PX4CT-MM-01, FE-PX4CT-MM-03, FE-PX4CT-MM-06 , FE-PX4CT-MM-10, FE-PX4CT-MM-12, FE-PX4CT-MM-15, FE-PX4CT-MM-20, FE-PX4CT-MM-25, FE-PX4CT-MM-35, FE-PX4CT-MM-50,		
Sales Category:	3.5MM & 2.5MM Cables and Adapters	Wire Gauge (AWG):	24 AWG
Connector A:	3.5mm TRRS 4 Conductor Male	Specification:	
Connector B:	3.5mm TRRS 4 Conductor Male	Number Ports:	N/A
Export Tariff Code (HST):	8544422000	Transfer Rate:	
Feature / Style:	4 Conductor	Images Length/Size Shown:	6 FT
# Positions:		Shielding:	Shielded
Convert From/To:		Type:	

Connects stereo audio & microphone devices requiring 4 conductors (left and right audio and microphone plus ground). This PREMIUM cable MAY also be suitable for left/right audio, 1 video (composite) and ground. This cable has a PVC jacket, metal shell ends with strain relief, and inner hood soldered 360 degrees This PREMIUM SHIELDED cable to protect against electron-magnetic outside interference, has gold plated end connectors, shielded copper (CU) stranded 24AWG cabling, and metal shell connectors designed to deliver PREMIUM AUDIO and MICROPHONE or VIDEO

Specifications:

- Connectors: 3.5mm (1/8") Male to Male Conductor TRRS
- Outer Diameter of Cable: 4.00mm
- Outer Diameter of Metal Shell: 8.4mm
- 4 Conductor, 24AWG Copper (CU)
- Gold Plated Connectors
- End to End shielding (Braided/Foil)
- Insulation Type: PVC 1.00mm
- Cable Spec: 24AWG 7/0.2BC*3C+AL+32/0.1BC OD:3.5MM
- RoHS-3 Compliant