MyCableMart_com

Your Home Theatre Connectivity Experts 6224 Bury Dr, Eden Prairie MN 55346 P. 952-486-8736

REVERSIBLE USB 2.0 TYPE A MALE TO MICRO-B 5-PIN CABLE, NICKEL PLATED





Lengths Available:	1.5ft, 3ft, 10ft,		
Colors Available:			
Part Numbers this model:	FE-USB-RACB5-01, FE-USB-RACB5-03, FE-USB-RACB5-10,		
Sales Category:	USB Cables	Wire Gauge (AWG):	24 AWG, 28 AWG
Connector A:	USB Standard Type A Male	Specification:	USB 2.0
Connector B:	USB Standard Type A Male	Number Ports:	N/A
Export Tariff Code (HST):	8544422000	Transfer Rate:	480Mbps
Feature / Style:	Data Transfer and Charge	Images Length/Size Shown:	3 FT
# Positions:		Shielding:	Shielded
Convert From/To:		Туре:	

USB A Male to Micro USB 5 pin Male Cable, Black. This REVERSIBLE USB A to REVERSIBLE Micro USB B 5pin Cable provides one USB A Male connector, and one Micro USB B connector to create a simple way to connect mobile devices to a USB capable computer for every day tasks such as data synchronization and file transfers. Never again will you have to fumble to figure out if your MICRO-B or USB TYPE-A connector ends are properly oriented for the device, computer, or charging block!

This cables is the most common USB cable used to charge and transfer data for many SMART-PHONES using the Android and Windows operating system.

When comparing our cables to our competitors, please note the WIRE THICKNESS of 28AWG (1P) + 24AWG*2C. Most of our competitors use 28/28AWG cables resulting in signal loss, slower charging times, and overall amperage loss. Both the USB Type-A connector AND the USB Micro-B connector are fully "reversible", meaning that you no longer have to connect this cable with the standard orientation, allowing for much quicker insertion (especially on the Micro-B connector end)

Cable Specifications:

- Cable Conductors Gauge: 28AWG (1P) + 24AWG*2C
- Shielding and Jacket Type: Aluminum foil shielding + drain wire 7/0.12mm pure copper
- Connector A: USB 2.0 Type A Reversible
- Connector B: USB 2.0 Micro-B 5pin Reversible
- Wire: CU (Pure Copper)
- RoHS Compliant
- Outer Cable Diameter: 4.5mm.