

DIGITAL/TOSLINK TO ANALOG 3.5MM AND 2 RCA CONVERTER AMPLIFIER VOLUME CONTROL



Lengths Available:			
Colors Available:			
Part Numbers this model:	ZT-T-609PRO		
Sales Category:	Optical Cables	Wire Gauge (AWG):	Not Specific / Not Applicable
Connector A:	RCA/Phono Female	Specification:	
Connector B:	RCA/Phono Female	Number Ports:	N/A
Export Tariff Code (HST):	8525503035	Transfer Rate:	
Feature / Style:		Images Length/Size Shown:	EA
# Positions:		Shielding:	
Convert From/To:		Type:	Toslink to RCA

This digital to analog audio converter is designed for home or professional audio switching and converting. It converts DIGITAL RCA COAX or TOSLINK OPTICAL audio signals to analog (left and right) audio. Optionally, you can connect 3.5mm audio headphones, and using the volume control knob, have perfect sound for your headphones. Ideal use for HDTVs that have digital audio outputs, and you need to output to your 3.5mm headphones!

TECH NOTE: Be sure your **SOURCE DEVICE** audio settings are set to **PCM AUDIO** (instead of Dolby or other format).

Features and Specifications:

- **INPUTS:** SPDIF Coax or Toslink Optical signals **SOURCE**
- **OUTPUTS to:** Analog Left and Right RCA or 3.5mm TRS Stereo
- Volume control knob with OFF position
- Supports 32kHz, 44.1kHz, 96kHz, and 192kHz to 24-bits
- 24-bit SPDIF incoming bit stream on left and right channels
- Supports 16-300 ohm headphones
- Power off switch
- Output Power (Max): 16ohms - 200mW, 300ohms - 20mW
- Size: 97x83x27mm
- Unit Weight: 118g
- Power Supply (included): 110v/5v DC / 500mA