

DIGITAL AUDIO (TOSLINK OR COAX) TO ANALOG AUDIO CONVERTER PLUS 3.5MM OUTPUT



Lengths Available:			
Colors Available:			
Part Numbers this model:	ZT-T-609S		
Sales Category:	Optical Cables	Wire Gauge (AWG):	Not Specific / Not Applicable
Connector A:	Toslink Optical Audio Female	Specification:	
Connector B:	Toslink Optical Audio Female	Number Ports:	N/A
Export Tariff Code (HST):	8525503035	Transfer Rate:	
Feature / Style:		Images Length/Size Shown:	EA
# Positions:		Shielding:	
Convert From/To:		Type:	Toslink to RCA

The Digital to Analog Audio Decoder will accept a 2 channel PCM digital audio input and output 2 channel analog audio. This product does not work with bitstream audio and/or will not downmix multichannel audio to stereo output.

Specifications

1. Input ports: 1 x Toslink/SPDIF, and 1 x Coaxial (RCA Type)
2. Output ports: 2 x RCA (Left/Right), 1 x 3.5mm Stereo Phone Jack.
3. Signal to Noise: 120db
4. Degree of Separation: 85db
5. Frequency Response: (20Hz ~ 20KHz) +/- 0.5db
6. Dimensions (mm): 72(D) x 55(W) x 20(H)
7. Weight (g): 40g

Contents

1. Main Unit (Digital to Analog decoder)
2. 5volt AC/DC Power Adapter (110/240v)
3. User Manual