



MARKING : Δ

550MHz (UL) E305668 TYPE CM 24AWG 75°C
 C(UL) E305668 CM 75°C ETL VERIFIED ANSI/TIA-568.2-D
 UTP CAT.6 RoHS COMPLIANCE MSL-VN- BATCH NO.

★ NOTE: All relevant materials are complied with RoHS directive .

8323-33		P1	P2	
1	1	1	1	WHITE/ORANGE
2	2	2	2	ORANGE
3	3	3	3	WHITE/GREEN
6	6	6	6	GREEN
4	4	4	4	BLUE
5	5	5	5	WHITE/BLUE
7	7	7	7	WHITE/BROWN
8	8	8	8	BROWN

3	MOLDED PVC BLACK	H1BP01-0304K07		M304
2	4 TWISTED PAIRS CAT.6 24AWG(7/0.19AS) UTP, OD 6.2mm, JACKET BLACK, DRAWING No. EU002404P-825	H5AJ57-0304K07	L+15mm	M304
1	8P8C MODULAR PLUG, GOLD PLATING 50μ" ON CONTACTS, TWO PIECES TYPE	A1NA70-0209	2	M209
No.	DESCRIPTION		Q'TY	Supplier
APPROVED		C6MB-XXX		Cable Length Unless Other Spec. Tolerances: 0 ~200mm ±10mm 201~1000mm ±20mm 1001 ~1500mm ±25mm 1501~2100mm ±30mm 2100mm± ±40mm
CHECKED	HU			
DESINGER	XJW			
DRAWING	WEI			
DATE	05/JUN/23	ITEM NO.		UNIT:mm