




PIN ASSIGNMENT:



NOTES:

1. 100%OPEN&SHORT TESTING
2. VOLTAGE:300V DC
3. INSULATION RESISTANCE:20M ohm
4. CONTACT RESISTANCE:5ohm

CUSTOMER P/N	length
FE-USB-ACB527-6IN	6(IN)150MM ± 20MM
FE-USB-ACB527-01	1.5(FT)450MM ± 30MM
FE-USB-ACB527-02	2(FT)500MM ± 30MM
FE-USB-ACB527-03	3(FT)905MM ± 30MM
FE-USB-ACB527-06	6(FT)1830MM ± 30MM
FE-USB-ACB527-10	10(FT)3050MM ± 50MM

8		
7		
6		
5		PE BAG+LABEL
4		PCV45Pa Black
3		MICRO-B USB 5PM
2		USB2.0 AM
1		USB2.0 cable 28AWG(7/0.12BC)*1P+24AWG(7/0.2BC) *2C+AL+D OD: 4.5mm Black
NO.	Material	Description

**MY CABLE MART LLC**

Title: <b>USB2.0 CABLE AM TO MICRO-B 5PM</b>			
Customer: MY CABLE MART LLC		Page: 1/1	Drawn BY: CLR
Customer P/N:		REV: A1	Check BY: DYH
Date: 2019.02.28	Drawing NO.: FUAM27	Unit: mm	Appd BY: