

7 6 5 4 3 2 1								
			ECN NO.	REV	DESCRIPTION	DATE	REVISER	APPROVED
PIN ASSIGNMENT: P1 1 2 3 4 SHELL P2 1 2 3 4 SHELL								
ELECTRICAL CHARACTER: 1.100% OPEN & SHORT TESTING. 2.WITHSTANDING VOLTAGE:DC 200V 0.01SEC. 3.INSULATION RESISTANCE:10M OHMS MIN. 4.CONDUCTIVE RESISTANCE:3 OHMS MAX.								
				GENERAL TOLERANCES (UNLESS SPECIFIED)		CUST PART NO.: My Cable Mart LLC		
3 PVC: BLACK g 10				.XXX: ±0.15		DESIGN: KEVIN		SCALE: NONE UNIT: mm THIRD ANGLE PROJECTION
2 CONN: USB AM,CONTACT: GOLD PLATED,SHELL: NICKEL PLATED W/TOP,BOTTOM SHELL, WHITE INSULATOR. PCS 2				.XX: ±0.25		CHECKED: KEVIN		TITLE: USB 2.0 AM TO AM CABLE
1 CABLE: 28AWG*1P + 24AWG*2C TC + braid 32*0.12mm CCAM OD: 4.5mm mm SEE TABLE 1				.X: ±0.50		APPROVED:		PART NO.: FS-USB-AA-6IN REV:A
ITEM DESCRIPTION UNIT QT'Y				SIZE DATE: 2010.06.12 A4 SHEET NO.: 1 OF 1				
7 6 5 4 3 2 1								