



REV.	DESCRIPTION	DATE	DESIGN
------	-------------	------	--------

PIN ASSIGNMENT:

P1	P2
1	1
2	2
3	3
4	4
5	5
6	6
7	7
8	8
9	9
Shell	Shell

- NOTES:**
- 100% OPEN & SHORT TEST
 - CONDUCTIVE RESISTANCE : 5 Ohms MAX
 - INSULATION RESISTANCE : 5M Ohms MIN
 - HI-POT : 300V DC/10ms
 - The product is ROHS compliant.

Client NO	GC-9F9M-06	GC-9F9M-10	GC-9F9M-15	GC-9F9M-25
Length	1830±30mm(6FT)	3050±50mm(10FT)	4580±50mm(15FT)	7620±80mm(25FT)

⑥	OUTER MOLDED	45P Black PVC	g	40	
⑤	INNER MOLDED	PE	g	12	
④	SCREW	Screw,Nickel Plater,	PCS	4	
③	CON	DB 9PIN Female Connector,Nickel Plated	PCS	1	
②	CON	DB 9PIN Male Connector,Nickel Plated	PCS	1	
①	CABLE	(30AWG+HDPE)*9C+D+AL+Black PVC OD:5.0mm	PC	1	
NO.	ITEM	DESCRIPTION	UNIT	Q'TY	Notes

		<h1>MY CABLE MART LLC</h1>							
X.±0.20						Drawing No.		JXD-VG1011/NI/BK/30AWG/CCS	
.X±0.15						REV	A/O	Title	DB 9P M-F
.XX±0.10		Scale	/	Customer	1-39	Checked			
Page 1/1		Item No.	-	Sales					
Unit	mm	Date	2021/10/26		Approval				