

8		7		6		5		4		3		2		1					
								REV.		DESCRIPTION				DATE		DESIGN			
L																			
High Speed HDMI™ Cable with Ethernet E358026 ㉿ AWM STYLE 20276 80°C 30V VW-1																			
E		PIN19 PIN18		TV		②		④⑤		①⑥		SOURCE		③		PIN2 PIN1			
D		PIN1 PIN2		P1		11.5±0.3		9.2±0.2		Ø15.0±0.2		⑤④		PIN18 PIN19		P2			
C		22.3±0.3		40.5±0.5		PIN Assignment 													
B		<p>1. Test Condition:</p> <p>(1) 100% OPEN & SHORT TEST;</p> <p>(2) Insulation Resistance: DC300V 5MΩ(Min) ;</p> <p>(3) Conductor Resistance: 5Ω/Max.</p> <p>(4) Hi-Pot:DC 300V/0.1s.</p> <p>2. The product is ROHS compliant.</p> <p>3. HDTV-DVD TEST:4K@60Hz</p>																	
A		<p>LOGO Size</p>																	
		Client NO		GC-HHL18-25		Length		7620±50mm(25FT)											
		⑥ MESH		Nylon Mesh		PCS		1		<p>MY CABLE MART LLC</p>									
		⑤ INNER MOLDED		PE		g		15											
		④ SHELL		HDMI AM zinc alloy Shell,Metal Gun Colour.		PCS		2											
		③ CON		HDMI AM Gold Plated Connector		PCS		1											
		② CON		HDMI AM Gold Plated Connector,with IC-HT8181		PCS		1											
		① CABLE		[(28AWG+FPE)*2C+D+HDPE+AL-foil]*5P+(28AWG+HDPE)*4C+AL+AEB+Black PVC OD7.3mm		PC		1											
		NO.		ITEM		DESCRIPTION		UNIT Q'TY		Notes		Unit mm		Date		2021/10/27		Approval	
8		7		6		5		4		3		2		1					