



1	2	3	4	5	6	7	8																		
Customer	Customer P/N:			<table border="1"> <tr> <th colspan="6">REVISIONS</th> </tr> <tr> <th>Rev.</th> <th>ECN No.</th> <th colspan="2">DESCRIPTION</th> <th>DATE</th> <th>APPROVED</th> </tr> <tr> <td> </td> <td> </td> <td> </td> <td> </td> <td> </td> <td> </td> </tr> </table>				REVISIONS						Rev.	ECN No.	DESCRIPTION		DATE	APPROVED						
REVISIONS																									
Rev.	ECN No.	DESCRIPTION		DATE	APPROVED																				

RoHS
compliant



P/N	L (M)	T (MM)	package quantity (PCS)	size of the pe bag A*B	carton size and material
FO3M-LCSC-1M	1	30	/	/	46*30*25 (K=K)
FO3M-LCSC-2M	2	50	/	/	46*30*25 (K=K)
FO3M-LCSC-3M	3	60	/	/	46*30*25 (K=K)
FO3M-LCSC-4M	4	60	/	/	46*30*25 (K=K)
FO3M-LCSC-5M	5	60	/	/	46*30*25 (K=K)
FO3M-LCSC-6M	6	80	/	/	46*30*25 (K=K)
FO3M-LCSC-7M	7	80	/	/	46*30*25 (K=K)
FO3M-LCSC-8M	8	100	/	/	46*30*25 (K=K)
FO3M-LCSC-9M	9	100	/	/	46*30*25 (K=K)
FO3M-LCSC-10M	10	100	/	/	46*30*25 (K=K)
FO3M-LCSC-15M	15	150	/	/	46*30*25 (K=K)
FO3M-LCSC-20M	20	200	/	/	46*30*25 (K=K)
FO3M-LCSC-25M	25	250	/	/	46*30*25 (K=K)



curing oven proportion: 10: 1
parameter: IL ≤ 0.3dB; PC/UPC RL ≥ 50dB, APC RL ≥ 60dB

4		
3	3.0mm Multimode Duplex OM3 50/125 Aqua pvc	1PCS
2	BLACK heat shrink TUBE, 4.0MM	2PCS
1	connector types: twin-core LC/PC-SC/PC connector	2PCS
NO.	DESCRIPTION	Q'TY

MRP				FILE.NO.			
				DAW.NO. F03M-LCSC-XX			
DESCRIPTION: FO3M-LCSC-XX		Rev	A/0		Unit	Scale	Date
		Page/NO.	1/2		mm	N.A	2015.5.10
Drawn by	HJ	Checked by			Approved by		